



DimWater Engineering builds gas treatment facilities for urban sewage and industrial wastewater. The contaminant removal process by scrubber is accomplished by neutralization reactions that eliminate acid and alkaline components.



- \bullet Removal of CL $_2$, HCL , NH $_3$ and other gases.
- Neutralization reactors made of GRP high reliability, durability efficiency and getting the best quality of emissions.
- Emissions completely odorless.
- Facilities designed and customized to customer needs.
- Elimination yields higher than 99%.
- Filler high efficiency.



Scrubber called to equipment, air purification through a process of washing, which removes contaminants in the gas itself.

This contributes to the reduction of emissions of alkaline gases like ammonia and acid gases such as chlorine below the levels stipulated in the Kyoto Protocols.

DimWater Engineering: union between manufacturing and engineering
We manufacture all equipment designed directly
by our engineering department.

Process

Single or dual systems, removing step depending on the contaminants to be removed.

- -Simple Stage: removing a contaminant (CL_2 o NH_3).
- **-Double Stage:** removing multiple alkaline pollutants (NH₃), acid (HCL) and other gases.

Accessories



Covers



We manufacture **custom covers for any type of construction** such as thickeners, mazes chlorination tanks ...

These fully removable covers, are designed depending on the type of cover to carry the load weight that can withstand exterior coat and color may decided by customer.

We manufacture **diameter between 1 meter and 30 meters.** We also manufacture square or rectangular covers with interior supports in GRP.

The covers may have accessories and color a customer chooses:

- Access manholes into Dn-500/600 PN 0.2, screwed
- Access manholes into special measures.
- Air inlet grille.
- Gas extraction sockets.
- Input sockets product.
- Detector sockets.

